


VECTOR I&Q MODULATOR - VMF-3F-2250 SQ

TECHNICAL FEATURE

FEATURES

- Space Qualified
- High Accuracy
- Hi-Rel Flatpack




PERFORMANCE

RF Input Frequency.....	2250 MHz (2200-2300MHz)
RF Input Power	+10 dB nom., +13 dB max.
I&Q Input Power Level	0 dBm max.
Conversion Loss.....	9 dB max.
	(below Modulation Input)
VSWR Input.....	1.5:1 max.
VSWR Output.....	2.0:1 max.
Impedance.....	50 Ohm nom.
Modulation Accuracy (measured @ 4 quadrants, 0 dBm input)	
Phase Balance	± 4° max.
Amplitude Balance	0.75 dB max.
Operating Temperature	-55° to +85° C

DESCRIPTION

I & Q modulators are integrated devices that produce linear phase modulation of an RF carrier. In the VMF Series, specially optimized circuits are used to provide superior performance across very wide bandwidths and high data rates. This has been designed, manufactured and qualified per Merrimac document CENG-0001, "Standard Design Requirements for Space Qualified Devices".

PACKAGE OUTLINE



- NOTES:
1. Tolerance on 3 place decimals ± .010(.25) except as noted.
 2. Dimensions in inches over millimeters.
 3. Dimensions marked with * apply only at body.
 4. All unmarked pins are case ground.

Crane Aerospace & Electronics
 Microwave Solutions – Merrimac Industries
 41 Fairfield Place, West Caldwell, NJ 07006
 + 1.973.575.1300 ext. 1309 • mw@crane-eg.com
 www.craneae.com/mw

VMF-3F-2223 SQ

