APPLICATION			REVISIONS							
NEXT A	SSY.	USE	D ON	REV		DES	CRIPTION	DATE	APPROVED	
				K	ECN 9730	1		06-19-97	FRANKEL	
				L	ECN 9906	9		02-24-99	FRANKEL	
				М	ECN 0028	0		10-05-00	FRANKEL	
				N	ECN 0314	3		06-23-03	RYAN	
				Р	ECN 0537	7		08-05-05	FRANKEL	
				R	ECN 0628	5		07-06-06	SEEGAR	
				Т	ECN 0648	4		11-20-06	RYAN	
				U	ECN 0703	5		01-19-07	SEEGAR	
			-	V	ECN 0735	3		09-14-07	SANDOVAL	
			-	W	ECN 0824	3		08-22-08	HOLLIDAY	
				Y	ECN 1000	79		03-25-10	SEEGAR	
				AA	ECN 1001	04		04-14-10	HOUSENGA	
				AB	ECN 1003	45		10-14-10	HOUSENGA	
				AC	ECN 1100	34		02-02-11	STEELMAN	
				AD	ECO 2013	-148		4-23-13	JENNINGS	
			-	AE	ECO 2013	8-234		6-17-13	JENNINGS	
			-	AF	ECO 2014	-314		9-3-14	JENNINGS	
			-	AG	ECO 2015-456			9/17/2015	5 JENNINGS	
			-	AH	ECO CC2	24-88	4	8/12/2024	RYAN	
			-							
			-							
			-							
						PROPRIETARY INFORMATION The information contained herein is proprietary to Co Aerospace & Electronics and shall not be reproduced disclosed in whole or in part or used for any design manufacture by Non-Crane Aerospace & Electron employees except when such user possesses direct wr authorization from Crane Aerospace & Electronics. Copyright © 2022 Crane Aerospace & Electronics – Proprie Information				
	PREPA	RED BY	DATE		CRANE		Propo Ela	otropic	o Inc	
	SCHRA	M	01/14/87		AEROSPACE & ELECTRONICS	l		GUIONIC	5, 1110.	
Ū 2∞	AMUSO		05/19/88	TITLE						
NG 1	APPRO	VED BY	DATE	1	QUALITY	Y CO	NTROL INSTRUCTIO	ON: QUALITY	CONTROL CODES	
AWII 24-	MODEL	=∟ NO.	06/22/87	SIZE	CAGE CO	DDE	DRAWING NO.	REV.	SHEET	
DR 911		соммо	Л	A	3302	25	91124-0008	AH	1 of 15	

1.0 SCOPE

1.1 <u>Purpose</u>

This document defines the Quality Control Codes required on all Purchase Orders and lists the required codes for each part category.

1.2 Applicability

This procedure is applicable to all purchase orders.

1.3 Supplier Notification

Upon any revision of this document, all suppliers will be notified of changes. Posting the current revision of this document to the Crane Aerospace and Electronics' website will be considered sufficient notification.

1.4 Notification of Changes

The Supplier shall notify Crane Aerospace & Electronics prior to any changes to the Suppliers or any sub-tier changes that affect purchase order requirements. A change is identified as any changes in company ownership, materials, configuration, process, sub-tier suppliers, inspection testing methods, techniques and/ or facility changes prior to the start of fabrication (notification is defined as a minimum of ninety (90) calendar days prior to change). Such changes or events may negate all previous Crane Aerospace & Electronics supplier qualifications, certifications, approval status, and may require re-qualification or resubmittal of a First Article.

2.0 APPLICABLE DOCUMENTS

2.1 Crane Electronics, Inc. Documents

08A30520-0001	Package Specification – Etched Substrates Chip Components
07A35627	Statement of Work (Hazeltine)
63A26349-0000	Hybrid MIC Workmanship Standards

2.2 <u>Government Documents</u>

Crane Electronics, Inc.	A	33025	91124-0008	AH	2	
	SIZE	CAGE CODE	DRAWING NO.	REV.	SHEET	
MIL-HDBK-1547	Electro	nic Parts, Materia	als, and Processes for Spa	ice and		
MIL-DTL-5541	Chemical Conversion Coating on Aluminum Alloys					
MIL-STD-1580	Destructive Physical Analysis for Space Quality Parts					
MIL-PRF-38534	Hybrid Microcircuits. General Specification for					
MIL-S-13949	Printed Wiring Board, General Specification for					
MIL-P-50884	Printed Wiring Flexible General Specification for					
	(Exclud	and Electronic	Initiated Explosive Devic	quipmer	IL TRIC	
MIL-STD-1686	Electro	static Discharge	Control Program for Prot	ection of	[• *	
	Electric	ally Initiated Exp	plosive Devices) METRI	È.		
MIL HDDK 205	and Ele	ctronic Parts, As	semblies and Equipment	(Excludi	ing	
MIL-FRF-55110 MIL-HDBK-263	Electro	static Discharge	Handbook for Protection	of Electr	rical	
MIL-SID-885 MIL DDE 55110	Drinted	Wiring Roards	lures for Microelectronics	5		
MIL-1-45208	Inspection System Requirements					
	-					

	Launch Vehicles
FED-STD-209	Clean Room and Work Station Requirements Controlled
	Environment
FED-STD-595	Color (Requirements for Individual Color Chips (3 x 5
	Supplements))

2.3 Industry Standards

ANSI/IPC A-610B	Acceptability of Printed Board Assemblies
ANSI/ASQC Q9000	Quality Systems
AS7108	NADČAP Audit Criteria for Chemical Processing
ISO 9002	Quality Management
ISO 9001	Quality Management System Requirements
AS9102	Aerospace First Article Inspection Requirements
AS9100	Quality Management System-Requirements for Aviation, Space, and
	Defense Organizations

3.0 QUALITY CONTROL CODES

CODE 17: Quality Management System

The Supplier shall have an established Quality Management System (QMS) that conforms to ISO9001 or AS9100. The Supplier's Quality Manual, procedures, and quality records shall be made available to Crane Electronics, Inc. for inspection, if requested.

CODE 18: Visual Inspection and Electrical Test

Supplier to certify that 100% electrical test in accordance with manufacturer's specifications, and 100% visual inspection in accordance with MIL-STD-883, Method 2010, 2017 or 2032, have been performed as applicable for Class "H" devices or approved manufacturer's workmanship standards.

CODE 19: Packaging Requirements

This order shall comply with the packaging requirements of Crane Electronics, Inc. specification 08A30520-0001.

CODE 20: First Article Inspection

The seller shall perform a First Article Inspection on Crane Electronics, Inc. controlled drawings and specifications unless otherwise specified by the Purchase Order or SOW.

First Article Inspection (FAI) shall conform to the requirements of Aerospace Standard AS9102, Aerospace First Article Inspection Requirement. The revision of this standard at the time of the purchase order applies.

In addition to the requirements of AS9102, the supplier is to be in compliance with the following paragraphs:

	SIZE	CAGE CODE	DRAWING NO.	REV.	SHEET
Crane Electronics, Inc.	Α	33025	91124-0008	AH	3

Specification Controlled Drawings, Off-The-Shelf, Commercial, Supplier or Supplier Item Drawings do not require a First Article Inspection, unless specifically stated on the Purchase Order.

First Article Clarifications: A documented First Article Verification is a requirement of this purchase order if:

- This order is the first to the supplier's facility or changes in manufacturing location for the part number identified on the purchase order; or if
- There is a change in drawing revisions, inspection methods, tooling, or materials with the potential of affecting form, fit, or function, a First Article Update is required for the area affected by the change only; or if
- There has been a 2-year or greater lapse in production (not applicable for Distributors); or if
- This is the first purchase order for this part number to call out First Article Verification, i.e., it is a new requirement.

Evidence of Supplier's First Article Verification documentation shall include:

- Recorded inspection and test variable data for all characteristics, requirements and parameters. The Supplier shall record all measurable characteristics (i.e., drawing dimension, tolerance, measured dimension, electrical tests, etc.), including a verification of drawing notes. If the report is not 100% complete, please explain omissions. The supplier shall forward a reproducible, signed copy of the report along with applicable material certifications (e.g., coating, paint, plating, composition, etc.) with the initial lot. Certifications are required for all items listed on the Crane Electronics, Inc. drawings or bills of material for the item or assembly purchased. Certifications for commercially available components used in the manufacture are not required to be submitted with the First Article but must be available upon request.
- Verification Quality Notes listed on the purchase order have been satisfied.
- First Article Verification Report shall include supplier name and be validated with an appropriate Quality Acceptance by stamp or signature and date of inspection. It must include purchase order number, part number, revision letter, drawing number, drawing and parts list revisions, and date code (if applicable).

The First Article sample shall have been fabricated using the same parts, materials and processes where production will be performed. A First Article shall not be performed on prototype parts unless specified by the Purchase Order.

	SIZE	CAGE CODE	DRAWING NO.	REV.	SHEET
Crane Electronics, Inc.	Α	33025	91124-0008	AH	4

NOTE: First Article Verification Report shall be shipped to Crane Electronics, Inc. with the deliverable lot.

NOTE: At the discretion of Crane Electronics, Inc., actual confirmation of the First Article Verification data at the supplier's plant may be required.

CODE 21: Printed Circuit Board Quality Requirements

Printed circuit board (PCB) suppliers shall have production and quality controls in place to produce PCBs that meet the requirements of IPC-A-600, IPC-A-6012 and as specified in the specific PCB drawing. Coupons, if required, for solderability testing shall be provided with each shipment. Coupons shall be from the same plating lot as the PCB's shipped.

CODE 22: Printed Circuit Board Assembly Quality Requirements

Printed circuit board assembly suppliers shall establish Electrostatic Discharge (ESD) controls in accordance with MIL-STD-1686 and MIL-HDBK-263. Workmanship Standards shall be in accordance with IPC-610 Class III, latest revision.

CODE 23: Microcircuit and Hybrid Quality Requirements

Microcircuit, hybrid module assembly workmanship, shall be controlled by the manufacturer and shall be in full compliance with Crane Electronics, Inc. Workmanship Standard 63A26349-0000. Electrostatic Discharge (ESD) controls, in accordance with MIL-STD-1686 and MIL-HDBK-263, are required.

CODE 24: Limited Life Materials

Items specified on this Purchase Order are shelf life limited and/or require temperature control. The supplier shall identify the product as applicable with the date of manufacture/temperature storage and shelf life requirements. Items shall have a minimum of 75% of the available shelf life remaining on the date of shipment to Crane Electronics, Inc.

CODE 25: Semiconductor, GaAs and Transistor Quality Requirements

Field Effect Transistors (FET's), MMIC's, SRD's, Varactors, and Bipolar Junction Transistors (BJTs), etc. Lot Acceptance Required (LAR). Wafer lot samples for electrical and bondability evaluation (approval) are required prior to any shipments. Total sample size shall be 20, (10) for bondability evaluation testing and (10) for RF testing. Bondability samples may be visual or electrical rejects from the same wafer lot number provided the bond pads meet dimensional/mechanical requirements. If the bondability samples are rejects, they shall be separately packaged from the RF samples and shall be marked "Bondability Samples". Bonding profile and accept/reject criteria shall be per MIL-STD-883, Method 2011, and as listed below:

Bonding Profile

- 1. Bonds must meet the MIL-STD-883, Method 2017 Visual Criteria.
- 2. Westbond 7416A Thermocompression Wedgebonder

SIZE

Heat Stage Temperature	:	170°C ±5°C
Tip Temperature	:	205°C to 215°C

Crane Electronics, Inc.

CAGE CODE DF 33025 9

Gram Force	:	20 to 25 grams
Time Delay on 1 st Bond	:	150 to 250 msec

Tool, DeWyle Tungsten Carbide: A-1/16-L-45-F-2010T = .012

Wire: .0007" Au, .5% to 1.5% elongation

Pass/Fail Criteria

- 1. Pass Wires that break at or above 2 grams that exhibit acceptable bonds.
- 2. Fail Any bond wire breakage or bond lift below 2 grams.
 - NOTE: Failures shall require process investigation and re-sampling before acceptance.

Lot Integrity

After the initial LAT (Lot Acceptance Test), if the wafer lot integrity is maintained, LAT shall not be repeated for subsequent shipments.

CODE 26: Wafer Lot Evaluation and Approval

Wafer lot samples for evaluation (approval) are required prior to any shipments for any wafer lot not previously approved by Crane Electronics, Inc.

CODE 27: Government Source Inspection

Government Source Inspection is required prior to shipment from your plant. Upon receipt of this order, promptly furnish a copy to the government representative who normally services your plant, so appropriate planning for government inspection can be accomplished. In the event the representative or office cannot be located, notify Crane Electronics, Inc. buyer immediately. Inspection and tests by the Government at the supplier's facility does not absolve the supplier of providing acceptable product or any subsequent rejections.

CODE 28: Plating Test Coupons

Test coupons shall be processed with the plating lot and shall be submitted with the lot. All parts shall be individually wrapped.

CODE 29: Certificate-of-Conformance (C-of-C)

- The Supplier shall provide a Certificate-of-Conformance (C-of-C) for each shipment of parts or material to Crane Electronics, Inc. The C-of-C shall list the following information:
 - Crane Electronics, Inc. purchase order number
 - The Crane Electronics, Inc. part number
 - The manufacturer's unique job or lot number, date, or date code (if applicable)
 - The sub-tier supplier's unique job or lot number, if applicable.

	SIZE	CAGE CODE	DRAWING NO.	REV.	SHEET
Crane Electronics, Inc.	Α	33025	91124-0008	AH	6

- Crane Electronics, Inc. shall be notified of non-conforming product. Nonconforming product shall be dispositioned by Crane Electronics, Inc., Crane Electronics, Inc.'s customer and/or government, as applicable, prior to shipment.
- The supplier shall notify Crane Electronics, Inc. of changes in product and/or process definition and obtain approval prior to changes. Product or process changes include changes in manufacturing location or manufacturing changes that affect form, fit, function, or reliability.
- Records: The supplier is required to maintain manufacturing records for a minimum of ten years, unless otherwise specified by purchase order. These records shall be available for review by Crane Electronics, Inc., Crane Electronics, Inc. customer and/or government agencies, as applicable.

CODE 30: Source Inspection Required

Crane Electronics, Inc. Source Inspection is required. Notify buyer ten (10) days in advance of shipment date to arrange for Crane Electronics, Inc. Source Inspection. Inspection and tests by Crane Electronics, Inc. or its customer at the supplier's facility or at our facility does not absolve the supplier of providing acceptable product or any subsequent rejections.

CODE 31: Wire Bonding Samples

Supplier shall supply ten (10) bonding samples. Visual/electrical rejects from the same wafer lot number may be used provided the bond pads meet dimensional/mechanical requirements. Bonding profile and accept/reject criteria shall be as listed below:

Bonding Profile

- 1. Bonds must meet the MIL-STD-883, Method 2017 Visual Criteria.
- 2. Westbond 7416A Thermocompression Wedgebonder

Heat Stage Temperature	:	$170^{\circ}C \pm 5^{\circ}C$
Tip Temperature	:	205°C to 215°C
Gram Force	:	20 to 25 grams
Time Delay on 1 st Bond	:	150 to 250 msec
-		

Tool, DeWyle Tungsten Carbide: A-1/16-L-45-F-2010T = .012

Wire: .0007" Au, .5% to 1.5% elongation

Pass/Fail Criteria

- 1. Pass Wires that break at or above 2 grams that exhibit acceptable bonds.
- 2. Fail Any bond wire breakage or bond lift below 2 grams.

CODE 32: Duroid Printed Circuit Board Quality Requirements

Duroid printed circuit board suppliers shall have production and quality controls that meet the requirements of MIL-P-13949 and the SCD.

CODE 33: Burrs on Machined Items

SIZECAGE CODEDRAWING NO.REV.SHEETCrane Electronics, Inc.A3302591124-0008AH7

Burrs, sharp projections or excess material located on the edges or corners of parent material: Any burrs, protrusions, or excess material that is visible under 10X magnification must be removed.

CODE 34: Flex Circuit Board Quality Requirements

Flex circuit board suppliers shall have production and quality controls that meet the requirements of MIL-PRF-31023 and the SCD.

CODE 35: Substrate Testing Requirements

Substrate Testing – All substrates shall be evaluated to the requirements of MIL-PRF-38534, Table VII. With the following additional requirements:

- a. Conductor Thickness shall be performed on sides A and B.
- b. Wirebond Evaluation shall be accomplished using the following profile:

Bonding Profile

Westbond 7416A Thermocompression Wedgebonder

Heat Stage Temperature Tip Temperature	:	170°C ±5°C 205° to 215°C
Gram Force Time Delay on 1 st Bond	:	20 to 25 grams 150 to 250 msec

Tool, DeWyle Tungsten Carbide: A-1/16-L-45-F-2010T = .012

Wire: .0007" Au, .5% to 1.5% elongation

c. Die Shear: The die attachment material shall be either AuGe or AuSn. Objective evidence of evaluation shall accompany each shipment.

CODE 36: Circuit Card Assemblies (CCA) Quality Requirements

CCA Assemblies (Hazeltine) - Statement of Work (SOW), 35627-0000, must be provided with each order.

CODE 37: Substrates With Thin-Film Resistors

Substrates - All resistor values must be adjusted by heat treat only. Laser trim is not acceptable unless otherwise specified in the applicable SCD.

CODE 38: Plating Surface Finish and Conditioning Suppliers

If the primary Supplier utilized sub-tier suppliers for special processes, such as plating, annealing, heat treating, or painting, the primary Suppliers Certificate-of-Conformance (C-of-C) shall indicate the sub-tier supplier's name and lot or run number. Contact the Crane Electronics, Inc. buyer for a list of approved processors.

The sub-tier suppliers performing plating, heat treating, painting or other processes shall provide a Certificate-of-Conformance (C-of-C) that list the Government, Military of Industry specification used to perform the special processing. These processes callout should exactly match the requirements of the Crane Electronics, Inc. drawing.

Crane Electronics, Inc.

SIZE CAGE CODE A 33025

CODE 39: External Lead and Termination Requirements

Pure tin finish is not permitted for External Lead/Termination finish. If the final layer contains tin; it must have a minimum of 3% Lead (Pb) by weight. Hot solder dip or tin-lead (Sn/Pb) plate is acceptable.

CODE 40: Prohibited Materials

Supplier shall not furnish products containing cadmium, zinc, mercury, or pure tin, unless otherwise specified on the SCD.

CODE 41: NADCAP Plating Requirements

Plating, surface finish, or conditioning shall be performed by an approved NADCAP accredited processor in the applicable plating, surface finish, or conditioning process.

CODE 42: Calibration Quality Requirements

Certificate of Calibration shall be attached along with the equipment verifying the following:

This instrument shall be calibrated to manufacturer specifications using standards which are traceable to the National Institute of Standards and Technology (NIST) and a quality system registered to IS09001 or AS9100.

Supporting documentation relative to traceability shall be kept on file.

CODE 43: Foreign Object Damage (FOD) Control

The supplier or sub-tier supplier shall maintain a Foreign Object (FO) Control program assuring work is accomplished in a manner preventing foreign objects, materials or debris from entering and remaining in finished housings, parts and PCB assemblies. Supplier shall be in compliance with AS9146, FOD Prevention Program, and establish and maintain written FOD Prevention Program Practices to reduce FOD. Supplier shall provide FO Control program training to employees performing operations on Crane Electronics, Inc. products. Maintenance of the work area and control of raw materials, metal shavings, tools, clippings and parts shall mitigate the risk of FO incidents.

CODE 44: Supplier Qualification

The supplier shall maintain strict control to ensure that, after the item(s) successfully pass the supplier qualification, no changes will be made to any design, material, part, process, procedure, fixtures, machines or machine setups, tooling or test equipment, measuring or aligning; nor shall they be altered, redesigned, or replaced by any other design, material, part, process procedure, tooling or test equipment, or the items shall not be produced at a facility other than the supplier's original facility which produced the acceptable items, without prior written approval by the Buyer.



The definition of change does not include the following: editorial or administrative changes such as spelling or typographical errors, clarifications, personnel, maintenance, or equipment changes not affecting the qualified product

CODE 45: Certificate-of-Analysis (C-of-A) Report

The supplier will include with each shipment the raw material manufacturer's Certificate-of-Analysis test report (e.g., mill test report) that states that the lot of material furnished has been tested, inspected, and found to be in compliance with the applicable material specifications. The test report will list the specifications, including revision numbers or letters, to which the material has been tested and/or inspected and the identification of the material lot to which it applies. When the material specification requires quantitative limits for chemical, mechanical, or physical properties, the test report will contain the actual test and/or inspection values obtained. For aluminum products, certifications for chemistry may indicate compliance within the allowed range. Certifications for physical properties will show actual values.

CODE 46: Supplier Access

Supplier shall provide accessibility to their facility for Crane Electronics, Inc.'s customers, as well as, their customers.

CODE 47: ESD Control

The supplier system shall have in place the requirements for an ESD control program in accordance with MIL-STD- 1686 or ANSI/ESD-S-20.20 to minimize the effects of ESD on parts, assemblies, and equipment.

CODE 48: ESD Class Zero

The supplier shall have in place the requirements and training for a "zero" ESD control plan in accordance with MIL-STD- 1686 or ANSI/ESD-S-20.20 to eliminate the effects of ESD on parts, assemblies & equipment.

CODE 49: Test/ Inspection Data

Supplier shall provide a complete set of Test/Inspection Data as recorded during acceptance test for purpose of quality analysis with each shipment.



CODE 50: Preference for Domestic Specialty Metals

This purchase order incorporates Crane Electronics, Inc. Group Purchase Order Terms and Conditions which impose requirements with which you must comply when filling this purchase order. In addition, this Purchase Order incorporates the following contract clauses (as applicable) which shall be flowed down to all of your suppliers that supply any articles delivered under this purchase order that include specialty metals.

DFARS 252.225-7008 Restriction on Acquisition of Specialty Metals

DFARS. 252.225-7009 Restriction on Acquisition of Certain Articles Containing Specialty Metals.

DFARS 252.225-7010 Commercial Derivative Military Article—Specialty Metals Compliance Certificate.

Exemptions to requirements of the above clauses may exist, as outlined in the clauses themselves or by operation of applicable Department of Defense Domestic Non-Availability Determinations (DNADs) posted on its public web site for that purpose (http://www.dcma.mil/dnad/) if you believe an exemption(s) apply, please specify the specifics and provide Crane with documents and information sufficient to demonstrate your entitlement thereto.

CODE 51: Prevention of Fungus Growth

All components, equipment or materials used in the procurement of stated purchased items must not result in the evidence of fungus growth on any surface. This requirement must be verified by analysis and/or test. The analysis to include supplier certifications of potentially fungus nutrient materials, if supplier certifications are unavailable a representative sample of exposed coatings, cables, gaskets, and other potentially fungus nutrient materials shall be subjected to MIL-STD-810, Method 508.5.

CODE 52: Supplier Flow-Down

ALL Quality Codes listed on the Crane Electronics, Inc. Purchase Order are required to be flowed down to the Suppliers sub-tiers, when used.

CODE 53: Tooling and/or Process Controls

	SIZE	CAGE CODE	DRAWING NO.	REV.	SHEET
Crane Electronics, Inc.	Α	33025	91124-0008	AH	11

Supplier shall notify the Crane Electronics, Inc. buyer for any of the following occurrences:

- Use of tooling that has not been in production for 1 year or more.
- Rework, refurbishment or replacement of any portion of the tooling used to produce the Purchase Order item.
- Any manufacturing process changes that alters the configuration, composition or physical properties of the produced item.
- Post notification the buyer will advise the supplier of a need for: First piece sample, new mold, die or tooling analysis.
- Buyer acceptance does not constitute acceptance of subsequent items or relieve the supplier from any obligations in compliance with the purchase order requirements.
- 4.0 PURCHASE ORDER (REQUISITION) REQUIREMENTS. Unless otherwise directed by Design, Manufacturing, or Quality Engineering, the following codes are the minimum required on each Purchase Order for the type of material being purchased:

Section	Description	Codes		
4.1	Electronic Components, Non-RF (Packaged, SMDs intended to	17, 29, 39,	40, 47	
	be soldered):			
	Integrated Circuits			
	Transistors			
	Diodes			
	Resistors			
	Capacitors			
	Inductors			
4.1.1	Electronic Components, RF (Packaged):	17, 29, 39, 40, 47		
	RF Integrated Circuits (RFICs)			
	MMICs	26 (as requ	ired by	
	Transistors	Engineerin	g)	
	RF Diodes	0	0)	
	Varactors			
	PINs			
	SRDs			
	Mixers			
	Detectors			
4.0	Etc.	17.20.40		
4.2	Miscellaneous Electrical/Mechanical Items:	17, 29, 40		
	Fasteners			
	Washers			
	Wire			
	Connectors			
	Etc.			
		-		

Section	Description			Codes	
4.3	Raw Material:			17, 29	
	Metal				
	Plastic				
	Liquids				
	Pastes				
	Etc.				
4.4	Plating			17, 28, 29, 3	8
4.5	Printed Circuit Boards:			17, 22, 39,	40, 46,
	Subcontract Assembly Supr	oliers		47, 52	
4.6	Hybrid Modules:			17, 23, 29,	39, 40,
	Subcontract Assembly Supr	oliers		43, 46, 47,	52
4.7	Printed Circuit Boards/Printed	Wiring Boards:		17, 21, 29,	40, 44,
	Manufacturing of PCBs (for	commodity Flex Circ	uits see	46, 52, 53	, ,
	4.18)				
	Rigid, Single, Double, Mult	i-Laver			
	Flexible, Single, Double, M	ulti-Laver			
	Rigid Flex, Single, Double.	Multi-Laver			
4.8	Electronic Components, Non-R	F (Die, Unnackaged	SMDs	17, 19, 29.	39, 40.
	intended for use in hybrid asser	nblies):		47	, ,
	Integrated Circuits)		•	
	Transistors			26 (as requ	ired by
	Diodes			Engineerin	<u>g</u>)
	Capacitors (MNOS, MNS, N	MOS, etc. only)			
4.9	Electronic Components (Die Unpackaged SMDs intended for			17, 19, 29,	39, 40,
	use in hybrid assemblies):	- np		47	
	Resistors			•	
	Capacitors (except MNOS,]	MNS, MOS, etc.)		26 (as requ	ired by
	Inductors			Engineerin	g)
4.10	Age and/or Temperature Contr	olled Items:		17, 24, 29	
	Epoxies				
	RTV				
	Loctite				
	Adhesives				
	Etc.				
4.11	Machined Parts:			17, 29, 33,	38, 40,
	Housings			43, 44, 45,	46, 52
	Covers			53	
	Base Plates				
	Panels				
	Brackets				
	Etc.				
	Si	ZE CAGE CODE	DRAWIN	IG NO.	REV.
			~		

Section	Description	Codes
4.11.1	Carriers:	17, 29, 33, 38, 44
	Kovar	45, 46, 52, 53
	W-Cu	
	Molybdenum	
	Steel	
	Etc.	
4.12	Paint Shops	17, 29, 38
4.13	Substrates, Ceramic	17, 19, 29, 35, 37
	Patterned	46, 52, 53
	Unpatterned	
	Alumina	
	BeO	
	Aluminum Nitride	
	Quartz	
	Sapphire	
	Etc.	
4.14	Customer Source Inspection (CSI)	30
4.15	Destructive Bond Pull Samples	31
4.16	Substrates, PTFE Based	17, 29, 32, 46, 52
	Patterned	53
	Unpatterned	
	Duroid	
	Polyflon	
	Rogers	
	Arlon	
	Etc.	
4.17	Electronic Components, RF (Die Unpackaged, SMDs intended	17, 29, 39, 40, 47
	for use in hybrid assemblies):	26. 11
	RF Integrated Circuits (RFICs)	26 (as required by
	MMICs	Engineering)
	Transistors	
4.18	Flex circuits (Commodity)	17, 29, 39, 40
4.19	Calibration	17, 42
4.20	"R" Part (Identified by Crane for solder dipping)	17, 29
	(Items with packaging prohibitive to solder dipping)	
4.21		17, 29, 46, 47, 48
	Beveriy/IVIET Reference	49, 50, 51, 52, 53



DRAWING NO. 91124-0008

CAGE CODE

33025