

# High Voltage DC-DC Converter

Input 490 - 930v: Output 28v: Power 4kW



## Multi-Market. Multi-Platform. Multi-Use

- Wide input voltage range supports more electric, hybrid-electric, and all-electric platforms
- >96% efficient, high power density conversion enables a light, sustainable, quieter aircraft
- Versatile 4kW power converter serves as power system's building block

Crane Aerospace & Electronics is an industry leader in power technology that accelerates the electrification of air, land and sea vehicles and systems. We've leveraged our more than 60 years of power expertise to deliver technology advancements that provide higher power in smaller and more efficient products.

By understanding the need of our performance-driven customers, Crane A&E engineers have designed and developed a uniquely versatile, modular High Voltage DC-DC Converter. Our one-of-a-kind converter delivers a wide input range that supports more-electric, hybrid-electric, and all-electric platforms. It supports multiple cooling options and converters can be paralleled to match a customer's power need.

Crane A&E's High Voltage DC-DC Converter converts high voltage source power into a power system's 28v DC bus. The converter is greater than 96% efficient and packs 4kW of power into a small package. As the commercial aviation and defense industries move toward alternative fuel sources, Crane A&E is positioned to meet demand with its multi-market, multi-platform, multi-use High Voltage DC-DC Converter.

### Multi-Market

- Commercial Aviation
- Defense

### Multi-Platform

- Turbine
- Electric
- Hybrid-Electric
- Hydrogen

### Multi-Use

- Distributed Bus Power
- Actuation, Motors and Fans
- Avionics



## Electrical Design Description

The power train of Crane's High Voltage DC-DC converter uses a highly efficient topology to minimize size, weight and dissipation.

Multiple modules are incorporated into the DC-DC converter. The input module serves as the high voltage electrical interface to the aircraft. It contains functions that ensure compliance with RF emissions, RF susceptibility, lightning and inrush current control. The supervisory module interfaces with aircraft control and monitoring functions. It provides protection and surveillance functions for the DC-DC converter.

## Performance Summary

KEY CHARACTERISTICS		
Electrical	Prototype 85-011	TSO 4-987-01
Input Voltage	90-800 Vdc	490-930 Vdc
Output Voltage Regulation	28 ± 0.5Vdc (nominal, can be configurable)	28 ± 0.5Vdc (nominal, can be configurable)
Output Ripple Voltage	<1.0V peak mean and mean valley	<1.0V peak mean and mean valley
Maximum Current	143 A	143 A
Output Power	4kW (parallel capable to increase power output)	4kW (parallel capable to increase power output)
Operating Temperature	-45 °C to +55 °C	-45 °C to +70 °C
Over Voltage Limit	Settable	Settable
Over Current Limit	Settable	Settable
EMI Filter	D0-160, Section 21, Cat. M	D0-160, Section 21, Cat. M
Cooling Method	Conduction, Self, or Liquid	Conduction, Self, or Liquid
Mechanical		
Weight	5.1 lbs (depends on cooling method selected)	6.9 lbs (depends on cooling method selected)
Environmental Protections	D0-160G	D0-160G
Dimensions (LxWxD)	12.24" x 6.04" x 1.525" (depends on cooling method selected)	12.6" x 7" x 2.4" (depends on cooling method selected)
Mounting Face Temperature	≤ +90 °C	≤ +90 °C
Converter Efficiency	≥ 96%	>96% for conduction and liquid cooled

Crane Aerospace & Electronics - Electrical Power Solutions [www.craneae.com/electrical-power-solutions](http://www.craneae.com/electrical-power-solutions)

ELDEC • Hydro-Aire • Interpoint • Lear Romec • Merrimac • P.L. Porter • Polyflon • Signal Technology  
16700 13th Avenue West • Lynnwood, WA 98037 • phone +1. 425.743.1313 • email: [info@craneae.com](mailto:info@craneae.com)

All technical information is believed to be accurate, but no responsibility is assumed for errors. We reserve the right to make changes in products or specifications without notice.  
Copyright © 2021 Crane Electronics, Inc. All rights reserved.