


# POLYFLON DESIGN DATA

## RF Variable Capacitors (0.3 - 25 pF)

- Non-Magnetic • High Voltage • High Power • High "Q"
- Screwdriver Adjust Rotating Piston Series

### RP Series



#### Design

PTFE anode and mount surfaces are metalized with electrodeposited copper. Polyflon's proprietary plating process eliminates the possibility of air being trapped between the PTFE and copper interface which could break down under voltage stress.

#### Specifications

Capacitance Range	0.3 - 25pF
Working Voltage	To 10Kv
Dielectric Strength	200% of working voltage
Quality Factor (Q)	5000 or greater
Insulation Resistance	10 <sup>6</sup> Megohms
Operating Temperature	-55° C to 125° C
Temperature Coefficient	50 ppm/° C
Tuning Torque	4 inch ounces (max.)

#### Notes

- 1 Working volts and maximum RMS current must not occur simultaneously.
- 2 Peak test voltage rating may be used for pulsed voltage applications. Peak pulsed current will be limited by the duty cycle that will provide an average current that does not exceed the maximum RMS current.
- 3 Mounting dimensions: 1/4" diameter "D" hole. Hardware: 1/4"-32 hex nut and internal tooth lockwasher. Mounting flange is at the bottom of the capacitor.

#### Lead Option Table

Lead Option	Description
05	without lead options
15	3" wire, top only - in line with flat
25	3" wire, top and bottom - in line with the flat
35	1 - 1/2" strap, top only - in line with the flat
65	3" wire, top only - opposite flat
75	3" wire, top and bottom - opposite flat
85	1 - 1/2" strap, top only - opposite flat

Ordering Instructions			
RP - VC	1 0 - 1 2 - 2 5		
Style	Kv(peak) test		
Max. capacitance rating expressed in picofarads (pF)	Lead Option		

PART NUMBER	Capacitance Range (pF)	Peak (Kv) Working Volts	Peak (Kv) Test Volts	Max. (RMS) Current (amps)	Dimensions/inch (mm)		Wt./Ounces (Approx.)
					L(+/- .020")	Dia.(+/- .020")	
RP - VC3 - 6 -*	0.3 - 3	3	6	0.70	0.800 (20.3)	0.375 (9.5)	0.10
RP - VC5 - 10 -*	0.8 - 5	5	10	2.40	1.250 (31.8)	0.500 (12.7)	0.25
RP - VC8 - 6 -*	3 - 8	3	6	1.90	0.870 (22.1)	0.560 (14.2)	0.25
RP - VC10 - 6 -*	0.8 - 10	3	6	1.70	1.150 (29.2)	0.375 (9.5)	0.20
RP - VC10 - 12 -*	0.8 - 10	6	12	3.40	1.530 (38.9)	0.625 (15.9)	0.75
RP - VC18 - 2 -*	0.8 - 18	1	2	1.70	1.150 (29.2)	0.420 (10.7)	0.20
RP - VC25 - 6 -*	5 - 25	3	6	5.50	1.430 (36.3)	0.875 (22.2)	1.00
RP - VC25 - 6B -*	5 - 25	3	6	3.90	1.540 (39.1)	0.625 (15.9)	1.00
RP - VC25 - 15 -*	5 - 25	10	15	7.20	1.770 (45.0)	1.250 (32.6)	1.75

\* See lead code on option table

**CRANE® POLYFLON**

Polyfon Company, One Willard Road, Norwalk, CT 06851 • Tel: (203) 840-7555 • Fax: (203) 840-7565  
Modem: (203) 840-7564 • Email: info@polyflon.com • http://www.polyflon.com