


# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

### FEATURES

- Small footprint, 0.79 in<sup>2</sup> (5.1 cm<sup>2</sup>) - MCH
- Surface mount package - MGH
- Operating temperature -55°C to +125°C
- 12 to 50 volt input
- Transient protection 80 volts for up to 120 ms  
70 volts for 15 volt single and dual models
- Fully isolated, magnetic feedback
- Fixed frequency switching
- Inhibit function
- Short circuit protection
- Undervoltage lockout
- Up to 79% efficiency, typical
- Soft-start function limits inrush current during start-up



| MODELS             |      |
|--------------------|------|
| OUTPUT VOLTAGE (V) |      |
| SINGLE             | DUAL |
| 5                  | ±5   |
| 12                 | ±12  |
| 15                 | ±15  |

### DESCRIPTION

The Interpoint® MCH Series™ and MGH Series™ of DC-DC converters offers up to 1.5 watts of power in a low profile package. The MCH/MGH converters are manufactured in our fully certified and qualified MIL-PRF-38534 Class H production facility and are packaged in hermetically sealed steel cases. They are ideal for use in programs requiring high reliability, small size, and high efficiency. The wide input voltage range of 12 to 50 volts accepts the varying voltages of military, aerospace, or space bus power and tightly regulates output voltages to protect downstream components. Transient protection of 80 volts for up to 120 milliseconds exceeds the requirements of MIL-STD-704A for the 5 and 12 volt single models and the 5 and 12 volt dual models. The 15 volt single and dual converters will withstand transients of up to 70 volts for up to 120 milliseconds.

The MCH and MGH converters are offered with standard screening, /ES, or /883 (MIL-PRF-38534 Class H). See Table 12 on page 14. Standard microcircuit drawings (SMD) are available. See Table 3 on page 4 and Table 8 on page 6.

### CONVERTER DESIGN

MCH Series and MGH Series of DC-DC converters incorporate a continuous flyback topology with a constant switching frequency of approximately 370 kHz. Current-mode pulse width modulation (PWM) provides output voltage regulation. Output error voltage is magnetically fed back to the input side of the PWM to regulate output voltage. Regulation is also affected by the load; refer to Table 10 on page 8 and Table 11 on page 9.

Dual models regulate the negative output with magnetic coupling to the positive output. Up to 80% of the total load may be on one output providing that the other output carries a minimum of 20% of the total load. The dual models can be used at double the output voltage by connecting the load between positive and negative outputs, leaving the common unconnected. (ex: MCH2805D can be used as a 10 volt output.)

### INHIBIT FUNCTION

MCH and MGH converters provide an inhibit terminal that can be used to disable internal switching, resulting in no output voltage and an input current as low as 2.3 mA. The converter is inhibited when the inhibit pin is pulled below 0.8 V and enabled when its inhibit pin is left floating. An external inhibit interface should be capable of pulling the converter’s inhibit pin below 0.8 V while sinking the maximum inhibit current and also allowing the inhibit pin to float high to enable the converter. A voltage should not be applied to the inhibit pin. The open circuit voltage present on the inhibit pin is 7 to 12 volts.

### PROTECTION FEATURES

Undervoltage lockout prevents the converters from operating below approximately 8 volts input voltage to keep system current levels smooth, especially during initialization or re-start operations. All models include a soft-start function to prevent large current draw and minimize overshoot. The converters also provide short circuit protection by restricting the current.

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

### MIL-STD-461

Use the Interpoint FMSA-461 (down-leaded) or FMGA-461 (surface mount, side-leaded) EMI filters to pass the CE03 requirements of MIL-STD-461C.

### PACKAGING

#### MCH - Down-leaded package

The MCH Series converters are packaged in hermetically sealed, projection-welded steel cases which provide EMI/RFI shielding. See Figure 20 on page 12.

#### MGH - Surface mount package

The surface mount MGH DC-DC converters can be mounted with pick-and-place equipment or manually. It is recommended that the case be attached with flexible epoxy adhesive or silicone which is thermally conductive (>1 watt /meter/°K).

Internal components are soldered with SN96 (melting temperature 221 °C) to prevent damage during reflow. Maximum reflow temperature for surface mounting the MGH converter is 220 °C for a maximum of 30 seconds. SN60, 62, or 63 are the recommended types of solder. Hand soldering should not exceed 300 °C for 10 seconds per pin.

The hermetically sealed metal cases are available in two different lead configurations. See Figure 21 on page 13 and Figure 22 on page 13.




FIGURE 1: MCH/MGH BLOCK DIAGRAM

# MCH and MGH Single and Dual DC-DC Converters


## 12 TO 50 VOLT INPUT – 1.5 WATT

| PIN OUT MCH MODELS |                 |                 |
|--------------------|-----------------|-----------------|
| Pin                | Single Output   | Dual Output     |
| 1                  | Positive Input  | Positive Input  |
| 2                  | Input Common    | Input Common    |
| 3                  | Positive Output | Positive Output |
| 4                  | Output Common   | Output Common   |
| 5                  | Case Ground     | Case Ground     |
| 6                  | No Connection   | Negative Output |
| 7                  | Inhibit         | Inhibit         |

TABLE 1: MCH PIN OUT

| MCH PINS NOT IN USE |                   |
|---------------------|-------------------|
| Inhibit             | Leave unconnected |
| “No Connection” pin | Leave unconnected |

TABLE 2: MCH PINS NOT IN USE



See Figure 20 on page 12 for dimensions.

FIGURE 2: MCH PIN OUT

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT




FIGURE 3: MCH MODEL NUMBERING KEY

| <b>SMD NUMBERS MCH MODELS</b>       |                  |
|-------------------------------------|------------------|
| STANDARD MICROCIRCUIT DRAWING (SMD) | MCH SIMILAR PART |
| 5962-9569601HXC                     | MCH2805S/883     |
| 5962-9569701HXC                     | MCH2812S/883     |
| 5962-9569801HXC                     | MCH2815S/883     |
| 5962-9570201HXC                     | MCH2805D/883     |
| 5962-9570301HXC                     | MCH2812D/883     |
| 5962-9570401HXC                     | MCH2815D/883     |

SMD numbers shown are for screening level Class H, standard case (X), standard pin seal and non-solder dipped pins (C). For other options please refer to the SMD for the SMD number and the vendor similar number. All SMD numbers are listed on the SMD in the "Bulletin" which is the last page of the SMD. For exact specifications for an SMD product, refer to the SMD. SMDs can be downloaded from <https://landandmaritimeapps.dla.mil/programs/smcr>

TABLE 3: MCH SMD NUMBER CROSS REFERENCE

| <b>MODEL NUMBER OPTIONS</b>   |                              |                 |                                |                                |                              |
|---|------------------------------|-----------------|--------------------------------|--------------------------------|------------------------------|
| <b>To DETERMINE THE MODEL NUMBER ENTER ONE OPTION FROM EACH CATEGORY IN THE FORM BELOW.</b> |                              |                 |                                |                                |                              |
| CATEGORY  | Base Model and Input Voltage | Output Voltage  | Number of Outputs <sup>1</sup> | Case Options <sup>2</sup>      | Screening <sup>3</sup>       |
| <b>OPTIONS</b>  | MCH28                        | 05, 12, 15      | S                              | MCH – down-leaded: leave blank | (standard, leave blank)      |
|   |                              | 05, 12, 15      | D                              |                                | ES<br>883                    |
| <b>FILL IN FOR MODEL #<sup>4</sup></b>  | <u>  MCH28  </u>             | <u>        </u> | <u>        </u>                | <u>        </u>                | <u>  /  </u> <u>        </u> |

Notes

- Number of Outputs: S is a single output and D is a dual output
- Case Options: For the standard MCH down-leaded case leave the case option blank.
- Screening: For standard screening leave the screening option blank. For other screening options, insert the desired screening level. For more information see Table 12 on page 14.
- If ordering MCH (down-leaded) case by model number add a "-Q" to request solder dipped leads (MCH2805S/883-Q).

TABLE 4: MCH MODEL NUMBER OPTIONS

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT


| <b>PIN OUT MGH MODELS</b> |                      |                    |
|---------------------------|----------------------|--------------------|
| <b>Pin</b>                | <b>Single Output</b> | <b>Dual Output</b> |
| 1                         | Positive Input       | Positive Input     |
| 2                         | No Connection        | No Connection      |
| 3                         | Input Common         | Input Common       |
| 4, 5                      | Positive Output      | Positive Output    |
| 6, 7                      | Case Ground          | Case Ground        |
| 8, 9                      | Output Common        | Output Common      |
| 10, 11                    | Case Ground          | Case Ground        |
| 12                        | No Connection        | No Connection      |
| 13, 14                    | No Connection        | Negative Output    |
| 15, 16, 17                | No Connection        | No Connection      |
| 18                        | Inhibit              | Inhibit            |

To meet specified performance for the MGH, all pins must be connected except "No connection" pins and Inhibit pin.

TABLE 5: MGH PIN OUT

| <b>MGH PINS NOT IN USE</b> |  |
|----------------------------|--|
| Inhibit                    | Leave unconnected  |
| "No Connection" pins       | Connect to case ground for best EMI performance. Also ok to leave unconnected. |

TABLE 6: MGH PINS NOT IN USE



Differently colored glass bead around pin one or dimple in header (bottom or side of case) indicates pin one.  
Cover marking is oriented with pin one at the upper right corner.

See Figure 21 on page 13 for dimensions and "gull-wing" option.

FIGURE 4: MGH PIN OUT

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT




FIGURE 5: MGH MODEL NUMBERING KEY

| <b>SMD NUMBERS MGH MODELS</b>       |                  |
|-------------------------------------|------------------|
| STANDARD MICROCIRCUIT DRAWING (SMD) | MGH SIMILAR PART |
| 5962-9569601HZA                     | MGH2805SZ/883    |
| 5962-9569701HZA                     | MGH2812SZ/883    |
| 5962-9569801HZA                     | MGH2815SZ/883    |
| 5962-9570201HZA                     | MGH2805DZ/883    |
| 5962-9570301HZA                     | MGH2812DZ/883    |
| 5962-9570401HZA                     | MGH2815DZ/883    |

SMD numbers shown are for screening level Class H, standard flat pack case (Z), standard pin seal and solder dipped pins (A). For other options please refer to the SMD for the SMD number and the vendor similar number. All SMD numbers are listed on the SMD in the "Bulletin" which is the last page of the SMD. For exact specifications for an SMD product, refer to the SMD. SMDs can be downloaded from <https://landandmaritimeapps.dla.mil/programs/smcr>

TABLE 7: MGH SMD NUMBER CROSS REFERENCE

| <b>MODEL NUMBER OPTIONS</b>  |                              |                |                                |  |                         |
|--|------------------------------|----------------|--------------------------------|--|-------------------------|
| TO DETERMINE THE MODEL NUMBER ENTER ONE OPTION FROM EACH CATEGORY IN THE FORM BELOW. |                              |                |                                |  |                         |
| CATEGORY   | Base Model and Input Voltage | Output Voltage | Number of Outputs <sup>1</sup> | Case Options <sup>2</sup>                  | Screening <sup>3</sup>  |
| <b>OPTIONS</b>   | MGH28                        | 05, 12, 15     | S                              | MGH – straight leads: leave blank          | (standard, leave blank) |
|  |                              | 05, 12, 15     | D                              | MGH – gull wings: Z (always solder-dipped) | ES<br>883               |
| <b>FILL IN FOR MODEL #<sup>4</sup></b>   | _MGH28_                      | _____          | _____                          | _____                                      | / _____                 |

**Notes**

- Number of Outputs: S is a single output and D is a dual output
- Case Options: For the MGH straight-lead case, leave the case option blank. For the surface mount gull-wing case, insert the letter "Z" in the case option position.
- Screening: For standard screening leave the screening option blank. For other screening options, insert the desired screening level. For more information see Table 12 on page 14.
- If ordering the MGH straight leads can be ordered "solder-dipped" by adding a Q to the model number - MGH2805S-Q. The MGH case Z is always solder-dipped.

TABLE 8: MGH MODEL NUMBER OPTIONS

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

TABLE 9: OPERATING CONDITIONS - ALL MODELS, 25 °C CASE, 28 VIN, UNLESS OTHERWISE SPECIFIED.

| PARAMETER   | CONDITIONS                              | ALL MODELS                          |           |      | UNITS           |
|---|---|-------------------------------------|-----------|------|-----------------|
|   |   | MIN                                 | TYP       | MAX  |                 |
| LEAD SOLDERING TEMPERATURE <sup>1</sup>   | 10 SECONDS MAX.                         | –                                   | –         | 300  | °C              |
| SURFACE MOUNT SOLDER REFLOW <sup>1, 2</sup>   | SN 60, 62 OR 63 RECOMMENDED             | 220 °C for max. of 30 seconds       |           |      |                 |
| STORAGE TEMPERATURE <sup>1</sup>  |   | -65                                 | –         | +150 | °C              |
| CASE OPERATING TEMPERATURE  | FULL POWER                              | -55                                 | –         | +125 | °C              |
|   | ABSOLUTE <sup>1</sup>                   | -55                                 | –         | +135 |                 |
| DERATING OUTPUT POWER/CURRENT <sup>1</sup>  | LINEARLY                                | From 100% at 125 °C to 0% at 135 °C |           |      |                 |
| ISOLATION: INPUT TO OUTPUT, INPUT TO CASE, OUTPUT TO CASE <sup>3</sup>                          | @ 500 VDC AT 25 °C                      | 100                                 | –         | –    | Megohms         |
| INPUT TO OUTPUT CAPACITANCE <sup>1</sup>  |   | –                                   | 100 - 170 | –    | pF              |
| UNDERVOLTAGE LOCKOUT <sup>1</sup>   |   | –                                   | 8         | –    | V <sub>IN</sub> |
| CURRENT LIMIT <sup>1, 4</sup>   | % OF FULL LOAD                          | –                                   | 125       | –    | %               |
| AUDIO REJECTION <sup>1</sup>  |   | –                                   | 40        | –    | dB              |
| SWITCHING FREQUENCY   | -55° TO +125 °C                         | 270                                 | 370       | 470  | kHz             |
| INHIBIT ACTIVE LOW (OUTPUT DISABLED)<br>Do not apply a voltage to the inhibit pin. <sup>5</sup> | INHIBIT PIN PULLED LOW                  | –                                   | –         | 0.8  | V               |
|   | INHIBIT PIN SOURCE CURRENT <sup>1</sup> | –                                   | –         | 1    | mA              |
|   | REFERENCED TO                           | INPUT COMMON                        |           |      |                 |
| INHIBIT ACTIVE HIGH (OUTPUT ENABLED)<br>Do not apply a voltage to the inhibit pin. <sup>5</sup> | INHIBIT PIN CONDITION                   | OPEN COLLECTOR OR UNCONNECTED       |           |      |                 |
|   | OPEN PIN VOLTAGE <sup>1</sup>           | 7                                   | –         | 12   | V               |

## Notes

1. Guaranteed by characterization test and/or analysis. Not a production test.
2. See Figure 22 on page 13 for more information
3. When testing isolation, input pins are tied together and output pins are tied together. They are tested against each other and against case. Discharge the pins before and after testing.
4. Dual outputs: The over-current limit will trigger when the sum of the currents from both outputs reaches 125% (typical value) of the maximum rated "total" current of both outputs.
5. An external inhibit interface should be used to pull the inhibit low or leave it floating. The inhibit pin can be left unconnected if not used.

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

TABLE 10: ELECTRICAL CHARACTERISTICS -55 °C TO +125 °C CASE, 28 VIN, 100% LOAD, UNLESS OTHERWISE SPECIFIED.

| MCH/MGH SINGLE OUTPUT MODELS          |                                    | MCH2805S<br>MGH2805S |      |      | MCH2812S<br>MGH2812S |       |       | MCH2815S<br>MGH2815S |       |       | UNITS  |
|---------------------------------------|------------------------------------|----------------------|------|------|----------------------|-------|-------|----------------------|-------|-------|--------|
| PARAMETER                             | CONDITIONS                         | MIN                  | TYP  | MAX  | MIN                  | TYP   | MAX   | MIN                  | TYP   | MAX   |        |
| OUTPUT VOLTAGE <sup>2</sup>           |                                    | 4.80                 | 5.00 | 5.20 | 11.52                | 12.00 | 12.48 | 14.40                | 15.00 | 15.60 | V      |
| OUTPUT CURRENT                        | V <sub>IN</sub> = 12 TO 50         | 0                    | –    | 300  | 0                    | –     | 125   | 0                    | –     | 100   | mA     |
| OUTPUT POWER                          | V <sub>IN</sub> = 12 TO 50         | 0                    | –    | 1.5  | 0                    | –     | 1.5   | 0                    | –     | 1.5   | W      |
| OUTPUT RIPPLE                         | T <sub>C</sub> = 25 °C             | –                    | 45   | 150  | –                    | 50    | 200   | –                    | 35    | 150   | mV p-p |
| 10 kHz - 2 MHz                        | T <sub>C</sub> = -55 °C TO +125 °C | –                    | 65   | 300  | –                    | 70    | 300   | –                    | 50    | 250   |        |
| LINE REGULATION                       | V <sub>IN</sub> = 12 TO 50         | –                    | 40   | 120  | –                    | 70    | 250   | –                    | 80    | 350   | mV     |
| LOAD REGULATION <sup>3</sup>          | 10% LOAD TO FULL                   | –                    | 380  | 800  | –                    | 640   | 1400  | –                    | 760   | 1600  | mV     |
| INPUT VOLTAGE                         | CONTINUOUS                         | 12                   | 28   | 50   | 12                   | 28    | 50    | 12                   | 28    | 50    | V      |
| NO LOAD TO FULL                       | TRANSIENT <sup>1</sup> 120 msec.   | –                    | –    | 80   | –                    | –     | 80    | –                    | –     | 70    |        |
| INPUT CURRENT                         | NO LOAD                            | –                    | 6.0  | 11   | –                    | 6.5   | 12    | –                    | 6.5   | 12    | mA     |
|                                       | INHIBITED                          | –                    | 2.4  | 3.5  | –                    | 2.4   | 3.5   | –                    | 2.4   | 3.5   |        |
| INPUT RIPPLE CURRENT <sup>4</sup>     | 10 kHz - 10 MHz                    | –                    | 130  | 250  | –                    | 150   | 250   | –                    | 150   | 250   | mA p-p |
| EFFICIENCY                            | T <sub>C</sub> = 25 °C             | 72                   | 77   | –    | 74                   | 79    | –     | 74                   | 79    | –     | %      |
|                                       | T <sub>C</sub> = -55 °C TO +125 °C | 69                   | 75   | –    | 72                   | 77    | –     | 72                   | 77    | –     |        |
| LOAD FAULT <sup>5, 6</sup>            | POWER DISSIPATION                  | –                    | 1.4  | 2.3  | –                    | 2.2   | 3.5   | –                    | 2.5   | 4.0   | W      |
| SHORT CIRCUIT                         | RECOVERY <sup>1</sup>              | –                    | 3.5  | 15   | –                    | 3.5   | 20    | –                    | 4.0   | 20    | ms     |
| STEP LOAD RESPONSE <sup>6, 7</sup>    | TRANSIENT                          | –                    | ±185 | ±500 | –                    | ±380  | ±800  | –                    | ±380  | ±800  | mV pk  |
| 50% - 100% - 50%                      | RECOVERY                           | –                    | 125  | 600  | –                    | 130   | 600   | –                    | 180   | 750   | µs     |
| STEP LINE RESPONSE <sup>1, 6, 8</sup> | TRANSIENT                          | –                    | 180  | ±500 | –                    | ±400  | ±1000 | –                    | ±450  | ±850  | mV pk  |
| V <sub>IN</sub> = 12 - 50 - 12        | RECOVERY                           | –                    | 0.75 | 4.0  | –                    | 0.6   | 3.0   | –                    | 0.5   | 2.5   | ms     |
| START-UP <sup>6</sup>                 | DELAY                              | –                    | 10   | 40   | –                    | 10    | 40    | –                    | 10    | 40    | ms     |
| V <sub>IN</sub> = 0 - 28, FULL LOAD   | OVERSHOOT <sup>1</sup>             | –                    | 0    | 150  | –                    | 0     | 350   | –                    | 0     | 450   | mV pk  |
| CAPACITIVE LOAD <sup>1, 9</sup>       | T <sub>C</sub> = 25 °C             | –                    | –    | 200  | –                    | –     | 200   | –                    | –     | 200   | µF     |

## Notes

- Guaranteed by characterization test and/or analysis. Not a production test.
- Specified at 50% total P<sub>out</sub>.
- Although no minimum load is required, at no load the output voltage may increase up to 15%.
- An external 2 µH inductor, added in series to the input, is necessary to maintain specifications.
- Load fault is a short circuit (<50 mohms). Maximum duration of short circuit: 25 °C - 90 seconds, 125 °C - 30 seconds. Recovery is into resistive full load.
- Recovery time is measured from application of the transient to point at which V<sub>out</sub> is within 1% of final value.
- Step load test is performed at 10 microseconds typical.
- Step line test is performed at 100 microseconds ± 20 microseconds.
- No effect on DC performance.



# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

TABLE 11: ELECTRICAL CHARACTERISTICS -55 °C TO +125 °C CASE, 28 VIN, 100% LOAD, UNLESS OTHERWISE SPECIFIED.

| MCH/MGH DUAL OUTPUT MODELS                                       |  | MCH2805D<br>MGH2805D |            |           | MCH2812D<br>MGH2812D |            |           | MCH2815D<br>MGH2815D |            |           | UNITS         |
|--|--|----------------------|------------|-----------|----------------------|------------|-----------|----------------------|------------|-----------|---------------|
| PARAMETER  | CONDITIONS                                       | MIN                  | TYP        | MAX       | MIN                  | TYP        | MAX       | MIN                  | TYP        | MAX       |               |
| OUTPUT VOLTAGE <sup>2</sup>                                      | $\pm V_{OUT}$                                    | 4.80                 | 5.00       | 5.20      | 11.52                | 12.00      | 12.48     | 14.40                | 15.00      | 15.60     | V             |
| OUTPUT CURRENT <sup>3</sup><br>$V_{IN} = 12$ TO 50               | EITHER OUTPUT                                    | 0                    | $\pm 150$  | 240       | 0                    | $\pm 62.5$ | 100       | 0                    | $\pm 50$   | 80        | mA            |
|  | TOTAL OUTPUT                                     | —                    | —          | 300       | —                    | —          | 125       | —                    | —          | 100       |               |
| OUTPUT POWER <sup>3</sup><br>$V_{IN} = 12$ TO 50                 | EITHER OUTPUT                                    | 0                    | $\pm 0.75$ | 1.2       | 0                    | $\pm 0.75$ | 1.2       | 0                    | $\pm 0.75$ | 1.2       | W             |
|  | TOTAL OUTPUT                                     | —                    | —          | 1.5       | —                    | —          | 1.5       | —                    | —          | 1.5       |               |
| OUTPUT RIPPLE<br>10 kHz - 2 MHz $\pm V_{OUT}$                    | $T_C = 25^\circ\text{C}$                         | —                    | 35         | 150       | —                    | 35         | 150       | —                    | 30         | 150       | mV p-p        |
|  | $T_C = -55^\circ\text{C TO } +125^\circ\text{C}$ | —                    | 50         | 250       | —                    | 40         | 250       | —                    | 35         | 250       |               |
| LINE REGULATION $\pm V_{OUT}$                                    | $V_{IN} = 12$ TO 50                              | —                    | 20         | 100       | —                    | 110        | 400       | —                    | 180        | 650       | mV            |
| LOAD REGULATION <sup>4</sup> $\pm V_{OUT}$                       | 10% LOAD TO FULL                                 | —                    | 350        | 700       | —                    | 570        | 1200      | —                    | 630        | 1400      | mV            |
| CROSS REGULATION <sup>5</sup>                                    | $-V_{OUT}$                                       | —                    | —          | 400       | —                    | —          | 500       | —                    | —          | 500       | mV            |
| INPUT VOLTAGE<br>NO LOAD TO FULL                                 | CONTINUOUS                                       | 12                   | 28         | 50        | 12                   | 28         | 50        | 12                   | 28         | 50        | V             |
|  | TRANSIENT <sup>1</sup> 120 msec.                 | —                    | —          | 80        | —                    | —          | 80        | —                    | —          | 70        |               |
| INPUT CURRENT  | NO LOAD  | —                    | 6.0        | 12        | —                    | 8.0        | 14        | —                    | 8.0        | 14        | mA            |
|  | INHIBITED  | —                    | 2.4        | 3.5       | —                    | 2.4        | 3.5       | —                    | 2.4        | 3.5       |               |
| INPUT RIPPLE CURRENT <sup>6</sup>                                | 10 kHz - 10 MHz                                  | —                    | 130        | 250       | —                    | 150        | 250       | —                    | 150        | 250       | mA p-p        |
| EFFICIENCY   | $T_C = 25^\circ\text{C}$                         | 73                   | 77         | —         | 73                   | 77         | —         | 72                   | 76         | —         | %             |
|  | $T_C = -55^\circ\text{C TO } +125^\circ\text{C}$ | 70                   | 75         | —         | 70                   | 75         | —         | 69                   | 74         | —         |               |
| LOAD FAULT <sup>6, 7</sup>                                       | POWER DISSIPATION                                | —                    | 1.6        | 2.5       | —                    | 2.7        | 4.2       | —                    | 3.0        | 4.5       | W             |
| SHORT CIRCUIT  | RECOVERY <sup>1</sup>                            | —                    | 3.8        | 20        | —                    | 3.2        | 20        | —                    | 4.0        | 20        | ms            |
| STEP LOAD RESPONSE <sup>7, 8</sup><br>50% - 100% - 50%           | TRANSIENT  | —                    | $\pm 140$  | $\pm 400$ | —                    | $\pm 260$  | $\pm 700$ | —                    | $\pm 270$  | $\pm 700$ | mV pk         |
|  | RECOVERY   | —                    | 100        | 500       | —                    | 165        | 800       | —                    | 50         | 300       | $\mu\text{s}$ |
| STEP LINE RESPONSE <sup>1, 7, 9</sup><br>$V_{IN} = 12 - 50 - 12$ | TRANSIENT  | —                    | $\pm 130$  | $\pm 300$ | —                    | $\pm 250$  | $\pm 600$ | —                    | $\pm 230$  | $\pm 600$ | mV pk         |
|  | RECOVERY   | —                    | 0.6        | 3.0       | —                    | 0.9        | 4.0       | —                    | 0.7        | 4.0       | ms            |
| START-UP <sup>7</sup><br>$V_{IN} = 0$ TO 28, FULL LOAD           | DELAY  | —                    | 10         | 45        | —                    | 10         | 45        | —                    | 10         | 45        | ms            |
|  | OVERSHOOT <sup>1</sup>                           | —                    | 0          | 150       | —                    | 0          | 350       | —                    | 0          | 900       | mV pk         |
| CAPACITIVE LOAD <sup>1, 10</sup>                                 | $T_C = 25^\circ\text{C}$                         | —                    | —          | 100       | —                    | —          | 100       | —                    | —          | 100       | $\mu\text{F}$ |

## Notes

- Guaranteed by characterization test and/or analysis. Not a production test.
- Specified at 50% total  $P_{OUT}$  with balanced loads.
- Up to 80% of the total output current/power is available from either output providing the opposite output carries a minimum of 20% total load.
- Although no minimum load is required, at no load the output voltage may increase up to 15%.
- Cross regulation is specified as the effect on  $-V_{out}$  for the following percentages of total output power:  $+P_o = 20\%$  and  $-P_o = 80\%$  to  $+P_o=80\%$  and  $-P_o=20\%$
- Load fault is a short circuit (<50 mohms). Maximum duration of short circuit:  $25^\circ\text{C} - 90$  seconds,  $125^\circ\text{C} - 30$  seconds. Recovery is into resistive full load.
- Recovery time is measured from application of the transient to point at which  $V_{out}$  is within 1% of final value.
- Step load test is performed at 10 microseconds typical.
- Step line test is performed at 100 microseconds  $\pm 20$  microseconds.
- No effect on DC performance.

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

TYPICAL PERFORMANCE PLOTS: 28 VIN, 25 °C CASE, 100% LOAD, UNLESS OTHERWISE SPECIFIED.

THESE ARE EXAMPLES FOR REFERENCE ONLY AND ARE NOT GUARANTEED SPECIFICATIONS.




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12




FIGURE 13

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

TYPICAL PERFORMANCE PLOTS: 28 VIN, 25 °C CASE, 100% LOAD, UNLESS OTHERWISE SPECIFIED.

THESE ARE EXAMPLES FOR REFERENCE ONLY AND ARE NOT GUARANTEED SPECIFICATIONS.




FIGURE 14




FIGURE 15




FIGURE 16




FIGURE 17




FIGURE 18





FIGURE 19

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

BOTTOM VIEW CASE A2



Weight 12 grams typical

Case dimensions in inches (mm)  
 Tolerance ±0.005 (0.13) for three decimal places  
 ±0.01 (0.3) for two decimal places  
 unless otherwise specified

**CAUTION**  
 Solder pins individually with heat application not exceeding 300°C for 10 seconds per pin.


- Materials
- Header Kovar/Nickel/Gold
  - Cover Kovar/Nickel
  - Pins Kovar/Nickel/Gold matched glass seal  
 Gold plating of 50 microinches, minimum,  
 included in pin diameter  
 Seal hole: 0.056 ±0.002 (1.42 ±0.05)

Please refer to the numerical dimensions for accuracy.



FIGURE 20: MCH CASE DIMENSIONS  
 DOWN-LEADED CASE

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT



The triangle (ESD) marking on the cover indicates pin one. Cover marking is oriented with pin one at the upper right corner. The straight lead configuration does not require a "case designator" in the model number. ex. MGH2805S



Weight 12 grams maximum

Case dimensions in inches (mm)

Tolerance  $\pm 0.005$  (0.13) for three decimal places,  $\pm 0.01$  (0.3) for two decimal places unless otherwise specified. Please refer to the numerical dimensions for accuracy.

**CAUTION**

Maximum reflow temperature is 220°C for a maximum of 30 seconds. SN60, SN62, or SN63 are the recommended types of solder. See MGH gull-wing solder pad layout. Hand soldering should not exceed 300°C for 10 seconds per pin.

**Materials**

|        |  |
|--------|--|
| Header | Kovar/Nickel/Gold  |
| Cover  | Kovar/Nickel   |
| Pins   | Kovar/Nickel/Gold matched glass seal                             |
|        | Gold plating of 50 - 150 microinches is included in pin diameter |
|        | Seal hole: 0.040 $\pm$ 0.002 (1.02 $\pm$ 0.05)                   |

Please refer to the numerical dimensions for accuracy.

FIGURE 21: MGH CASE DIMENSIONS



Dimensions in inches (mm)

Tolerance  $\pm 0.005$  (0.13) for three decimal places  $\pm 0.01$  (0.3) for two decimal places, unless otherwise specified. Please refer to the numerical dimensions for accuracy.

**CAUTION:**

Internal components are soldered with SN96 (melting temperature 221°C) to prevent damage during reflow. Maximum reflow temperature for surface mounting the MGH converter is 220°C for a maximum of 30 seconds. SN60, 62, or 63 are the recommended types of solder.

Hand soldering should not exceed 300°C for 10 seconds per pin.

**SOLDER MASK NOTES**

1. Pad dimensions are for the solder mask. Leads common to each other can be connected to each other as desired.
2. Ground (case) pins should be connected to the center pad for improved grounding.
3. Connect "no connection" pins to case ground to reduce EMI.
4. Center pad should not have a solder mask.
5. Adhesive attach is intended to be a surface for soldering the hybrid to the circuit board.
6. Pre-tin base of converter prior to soldering.
7. If less rotation of case is desired, reduce the width of the large case pad by 0.020 inches (0.51 mm). Pad length can be extended 0.010 inches (0.25 mm) towards the case body and an as-desired dimension away from the case body.
8. Do not exceed 220°C as measured on the body of the converter (top or bottom).
9. Attach the body of the case to the board with a thermally conductive adhesive or SN60, 62, or 63 solder. The adhesive can be electrically conductive as well. It can be applied as an underfill post solder or dispensed and cured prior or during solder.
10. In the presence of vibration, to ensure reliable mechanical attachment, the body of the case should be attached with adhesive or solder as noted above (note 7). The leads alone do not provide sufficient mechanical attachment.

FIGURE 22: MGH GULL-WING SOLDER PAD LAYOUT

SURFACE MOUNT CASE AND LEAD OPTIONS

# MCH and MGH Single and Dual DC-DC Converters

## 12 TO 50 VOLT INPUT – 1.5 WATT

ELEMENT EVALUATION TABLES FOR QML PRODUCTS ARE IN “APP-009 QUALITY AND CERTIFICATION”, APPENDIX A, IN COMPLIANCE WITH MIL-PRF-38534 REVISION L.  
( LINK [HTTPS://WWW.CRANEAE.COM/QUALITY-ASSURANCE-MODULAR-POWER](https://www.craneae.com/quality-assurance-modular-power) )

### ENVIRONMENTAL SCREENING HIGH RELIABILITY STANDARD, /ES, /SX AND /883 (CLASS H)

| TEST PERFORMED   | NON-QML <sup>1</sup> |     |                  | CLASS H<br>QML <sup>2, 3</sup> |
|--|----------------------|-----|------------------|--------------------------------|
|  | STANDARD             | /ES | /SX <sup>4</sup> | /883                           |
| <b>Pre-cap Inspection, Method 2017, 2032</b>                   | ■                    | ■   | ■                | ■                              |
| <b>Temperature Cycle (10 times)</b>                            |                      |     |                  |                                |
| Method 1010, Cond. C, -65 °C to +150 °C, ambient               |                      |     | ■                | ■                              |
| Method 1010, Cond. B, -55 °C to +125 °C, ambient               |                      | ■   |                  |                                |
| <b>Constant Acceleration</b>                                   |                      |     |                  |                                |
| Method 2001, 3000 g  |                      |     | ■                | ■                              |
| Method 2001, 500 g   |                      | ■   |                  |                                |
| <b>PIND, Test Method 2020, Cond. A</b>                         |                      |     | ■ <sup>5</sup>   | ■ <sup>5</sup>                 |
| <b>Burn-in Method 1015, +125 °C case, typical <sup>6</sup></b> |                      |     |                  |                                |
| 96 hours   |                      | ■   |                  |                                |
| 160 hours  |                      |     | ■                | ■                              |
| <b>Final Electrical Test, MIL-PRF-38534, Group A,</b>          |                      |     |                  |                                |
| Subgroups 1 through 6, -55 °C, +25 °C, +125 °C case            |                      |     | ■                | ■                              |
| Subgroups 1 and 4, +25 °C case                                 | ■                    | ■   |                  |                                |
| <b>Hermeticity Test, Method 1014</b>                           |                      |     |                  |                                |
| Gross Leak, Cond. C <sub>1</sub> , fluorocarbon                |                      | ■   | ■                | ■                              |
| Fine Leak, Cond. A <sub>2</sub> , helium                       |                      | ■   | ■                | ■                              |
| Gross Leak, Dip  | ■                    |     |                  |                                |
| <b>Final visual inspection, Method 2009</b>                    | ■                    | ■   | ■                | ■                              |

Test methods are referenced to MIL-STD-883 as determined by MIL-PRF-38534.

#### Notes

1. Non-QML products may not meet all of the requirements of MIL-PRF-38534.
2. All processes are QML qualified and performed by certified operators.
3. A QML products which has an SMD number is marked “QML”. A QML product which does not have an SMD number is marked per MIL-PRF-38534 table III.
4. “SX” screening is performed per MIL-PRF-38534, MIL-STD-883, Class H for non-QML devices.
5. Not required by DLA but performed to assure product quality.
6. Burn-in temperature designed to bring the case temperature to +125 °C minimum. Burn-in is a powered test.

TABLE 12: ENVIRONMENTAL SCREENING HIGH RELIABILITY STANDARD, /ES AND /883 (CLASS H)